



according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 2

Print date: 21.11.2014

Product code: 765001

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Lube Oil RL 2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant and additive.

1.3. Details of the supplier of the safety data sheet

| Company name: | ADDINOL Lube Oil GmbH | |
|--|---|-------------------------------|
| | Gebäude 4609 | |
| Street: | Am Haupttor | |
| Place: | D-06237 Leuna | |
| Telephone: | +49 (0) 3461 845-201 | Telefax: +49 (0) 3461 845-561 |
| e-mail: | info@addinol.de | |
| Contact person: | Application Technology | |
| Internet: | www.addinol.de | |
| Responsible Department: | ADDINOL Application Technology | |
| 1.4. Emergency telephone | +49 (0) 3461 845-201 - This number is serviced during office hours. | |
| and the second s | | |

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xn - Harmful R phrases: Harmful: may cause lung damage if swallowed.

GHS classification

Hazard categories: Aspiration hazard: Asp. Tox. 1 Hazard Statements: May be fatal if swallowed and enters airways.

2.2. Label elements

Hazardous components which must be listed on the label

Contains: Distillates (petroleum), hydrotreated light.

| Signal word: | Danger |
|--------------|--------|
| Pictograms: | GHS08 |
| | |

Hazard statements

H304

May be fatal if swallowed and enters airways.

Precautionary statements

| P102 | Keep out of reach of children. |
|-----------|--|
| P103 | Read label before use. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P331 | Do NOT induce vomiting. |
| P405 | Store locked up. |
| | • |



according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 2

Print date: 21.11.2014

Product code: 765001

Page 2 of 7

Additional advice on labelling

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Process vapors can irritate airways, skin and eyes. Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| EC No | Chemical name | Quantity |
|------------|---|----------|
| CAS No | Classification | |
| Index No | GHS classification | |
| REACH No | | |
| 265-149-8 | Distillates (petroleum), hydrotreated light | < 99 % |
| 64742-47-8 | Xn - Harmful R65 | |
| | Asp. Tox. 1; H304 | |

Full text of R and H phrases: see Section 16.

Further Information

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do not induce vomiting. Rinse mouth thoroughly with water. Immediately get medical attention.

Caution if victim vomits: Risk of aspiration!

4.2. Most important symptoms and effects, both acute and delayed

Following symptoms can occur: Coughing. difficulties of breathing.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.



according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 2

Print date: 21.11.2014

Product code: 765001

Page 3 of 7

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water. Sand.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. Phosphorus oxides. Carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not empty into drains or the aquatic environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear respiratory protection when in the presence of vapour, dust, and aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well ventilated zones or use proper respiratory protection. Avoid oil mist In case of open handling equipment with built-in suction must be used. Avoid contact with skin, eye and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Provide adequate ventilation. When hot, product develops flammable vapours.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of dampness. Keep container tightly closed in a cool place.

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.



according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 2

Print date: 21.11.2014

Product code: 765001

Page 4 of 7

Further information on storage conditions

Recommended storage temperature: 10 - 30°C Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: refer to Technical Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Recommended limit value for oil mist TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65° C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm



according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 2

Print date: 21.11.2014

Product code: 765001

Page 5 of 7

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state: | liquid |
|-----------------|--------------------|
| Colour: | yellow |
| Odour: | like: mineral oil. |

Changes in the physical state

| Initial boiling point and boiling range: |
|--|
| Flash point: |
| Ignition temperature: |
| Density (at 15 °C): |
| Water solubility: |
| Viscosity / kinematic: (at 40 °C) |

Test method

No data available 106 °C DIN EN ISO 2719 No data available 0,843 g/cm³ DIN 51757 virtually insoluble 3,90 mm²/s DIN 51562

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable with proper care and handling.

10.2. Chemical stability

The product is chemically stable when handled and stored under normal conditions.

10.3. Possibility of hazardous reactions

No decomposition if used as intended.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with : Oxidizing agents, strong.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. Phosphorus oxides. Carbon black.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No data available

Mixture not tested.

Irritation and corrosivity

Irritant effect on the skin: mild irritant.

Irritant effect on the eye: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Sensitising effects

Evaluation: no danger of sensitization.

Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Carcinogenic/mutagenic/toxic effects for reproduction



according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 2

Print date: 21.11.2014

Product code: 765001

Page 6 of 7

No data available

Specific effects in experiment on an animal

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

Mixture not tested.

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

Waste disposal number of waste from residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils

Classified as hazardous waste.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning. Waste disposal according to official state regulations. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

| <u>14.1. UN number:</u> | - |
|-----------------------------------|----|
| Inland waterways transport (ADN) | |
| <u>14.1. UN number:</u> | - |
| Marine transport (IMDG) | |
| <u>14.1. UN number:</u> | - |
| 14.3. Transport hazard class(es): | - |
| Marine pollutant: | no |



according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 2

Print date: 21.11.2014

Product code: 765001

Page 7 of 7

Air transport (ICAO)

14.1. UN number:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

Other applicable information

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

1 - slightly water contaminating

Water contaminating class (D): 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

Harmful: may cause lung damage if swallowed.

Full text of H statements referred to under Sections 2 and 3

May be fatal if swallowed and enters airways.

Further Information

65

H304

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contructual relationship.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)