



**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 680**

Revision date: 29.07.2024

Product code: 741015

Page 2 of 11

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
9003-29-6	Polybutenes			5 - < 10 %
	500-004-7			
	Asp. Tox. 1; H304			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic			1 - < 2.5 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
68937-96-2	Di-tert-butyl-Polysulfides			0.5 - < 1 %
	273-103-3		01-2119540515-43	
	Skin Sens. 1B, Aquatic Chronic 3; H317 H412			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
9003-29-6	500-004-7	Polybutenes	5 - < 10 %
		inhalation: LC50 = 4820 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 mg/kg	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic	1 - < 2.5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
68937-96-2	273-103-3	Di-tert-butyl-Polysulfides	0.5 - < 1 %
		Skin Sens. 1B; H317: >= 46 - 100	

**Further Information**

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Gear Oil CLP 680

Revision date: 29.07.2024

Product code: 741015

Page 3 of 11

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

#### **Unsuitable extinguishing media**

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. carbon black.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### 6.3. Methods and material for containment and cleaning up

#### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

#### **Advice on general occupational hygiene**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 680**

Revision date: 29.07.2024

Product code: 741015

Page 4 of 11

**Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

**Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

**Further information on storage conditions**

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 5 - 40°C

**7.3. Specific end use(s)**

Further information: see technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic			
	Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>
	Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
68937-96-2	Di-tert-butyl-Polysulfides			
	Worker DNEL, long-term	inhalation	systemic	3,29 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	4,67 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,58 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	1,67 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,167 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 680**

Revision date: 29.07.2024

Product code: 741015

Page 5 of 11

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
Secondary poisoning		9,33 mg/kg
68937-96-2	Di-tert-butyl-Polysulfides	
Freshwater		0,00024 mg/l
Freshwater (intermittent releases)		0,002 mg/l
Marine water		0,000024 mg/l
Freshwater sediment		0,94 mg/kg
Marine sediment		0,094 mg/kg
Secondary poisoning		6,66 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,51 mg/l
Soil		0,0181 mg/kg

**Additional advice on limit values**

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

**Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

**Skin protection**

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be

## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Gear Oil CLP 680

Revision date: 29.07.2024

Product code: 741015

Page 6 of 11

worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	brown
Odour:	like: mineral oil.
Odour threshold:	not determined

#### Test method

Melting point/freezing point:	No data available	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	No data available	
Lower explosion limits:	No data available	
Upper explosion limits:	No data available	
Flash point:	280 °C	DIN EN ISO 2592
Auto-ignition temperature:	not determined	
Decomposition temperature:	No data available	
pH-Value:	not applicable	
Viscosity / kinematic: (at 40 °C)	670 mm <sup>2</sup> /s	ASTM D 7042
Water solubility:	virtually insoluble	
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:	No data available	OECD 123
Vapour pressure:	No data available	
Density (at 15 °C):	0,905 g/cm <sup>3</sup>	DIN 51757
Relative vapour density:	No data available	
Particle characteristics:	No data available	

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties	
No data available	
Self-ignition temperature	
Solid:	No data available
Gas:	No data available
Oxidizing properties	
No data available	

#### Other safety characteristics

Evaporation rate:	No data available
Pour point:	-12 °C ASTM D 7346

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 680**

Revision date: 29.07.2024

Product code: 741015

Page 7 of 11

**10.4. Conditions to avoid**

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

**10.5. Incompatible materials**

Reacts with: Oxidising agent, strong

**10.6. Hazardous decomposition products**In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. carbon black. No known hazardous decomposition products.**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**Based on available data, the classification criteria are not met.  
Mixture not tested.**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
9003-29-6	Polybutenes				
	oral	LD50 > 10000 mg/kg	Rat	Study report (1986)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 4820 mg/l	Rat		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402

**Irritation and corrosivity**Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**Based on available data, the classification criteria are not met.  
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 680**

Revision date: 29.07.2024

Product code: 741015

Page 8 of 11

**Endocrine disrupting properties**

not applicable

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
9003-29-6	Polybutenes					
	Acute fish toxicity	LC50 > 1,55 mg/l	96 h	Cyprinus carpio	Other company data (2002)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 19,2 mg/l	72 h	Desmodesmus subspicatus	Other company data (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 3,1 mg/l	48 h	Daphnia magna	Study report (2000)	OECD Guideline 202
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h			
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
68937-96-2	Di-tert-butyl-Polysulfides					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Raphidocelis subcapitata	Study report (2012)	OECD Guideline 201
	Acute crustacea toxicity	EL50 63 mg/l	48 h	Daphnia magna	Study report (2013)	OECD Guideline 202

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
9003-29-6	Polybutenes	7,6 - 7,8
68937-96-2	Di-tert-butyl-Polysulfides	5,6

**BCF**

CAS No	Chemical name	BCF	Species	Source
9003-29-6	Polybutenes	314 - 1882		USEPA (2008)
68937-96-2	Di-tert-butyl-Polysulfides	0,006	Lepomis macrochirus	Study report (2015)

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**



## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Gear Oil CLP 680

Revision date: 29.07.2024

Product code: 741015

Page 9 of 11

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

No data available

#### **Further information**

Do not allow uncontrolled leakage of product into the environment.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

##### **List of Wastes Code - residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

##### **Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

#### **Inland waterways transport (ADN)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

#### **Marine transport (IMDG)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

#### **Air transport (ICAO-TI/IATA-DGR)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

#### **14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

#### **Other applicable information**

No dangerous good in sense of these transport regulations.

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 680**

Revision date: 29.07.2024

Product code: 741015

Page 10 of 11

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,3,6,8,9.

**Abbreviations and acronyms**

Asp. Tox: Aspiration hazard

Skin Sens: Skin sensitisation

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Relevant H and EUH statements (number and full text)**

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

**Further Information**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 680**

Revision date: 29.07.2024

Product code: 741015

Page 11 of 11

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*