



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 2 of 10

	smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to a waste disposal system.

Additional advice on labelling

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
203-448-7	butane	< 30 %
106-97-8	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1; H220	
200-827-9	propane	< 15 %
74-98-6	F+ - Extremely flammable R12	
601-003-00-5	Flam. Gas 1; H220	
926-141-6	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	< 15 %
64742-47-8	Xn - Harmful R65-66	
	Asp. Tox. 1; H304	
01-2119456620-43		
273-066-3	Triaryl phosphate isopropylated	< 1 %
68937-41-7	N - Dangerous for the environment R51-53	
	Aquatic Chronic 2; H411	
204-112-2	Triphenyl phosphate	< 1 %
115-86-6	N - Dangerous for the environment R50-53	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410	

Full text of R and H phrases: see Section 16.

Further Information

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move victim out of danger zone and lay down. Position and transport victim on their side. In case of



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 3 of 10

respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen. In case of irritation of the respiratory tract seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Do not induce vomiting.

Rinse mouth thoroughly with water. Immediately get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Atomized water. Carbon dioxide (CO₂). Extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x). Carbon black.

Flammable. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not empty into drains or the aquatic environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Guide people to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 4 of 10

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray into flames or ignition sources. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eye and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of dampness. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature: 10 - 30°C. Do not store at temperatures over: 50°C.

7.3. Specific end use(s)

Further information: refer to Technical Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
115-86-6	Triphenyl phosphate	-	3		TWA (8 h)	WEL
		-	6		STEL (15 min)	WEL

Additional advice on limit values

source:

8.2. Exposure controls



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 5 of 10



Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing.

Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	gaseous
Colour:	light yellow
Odour:	characteristic

Test method

Changes in the physical state

Flash point: < -20 °C DIN EN ISO 2592

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Lower explosion limits:	0,5 vol. %
Upper explosion limits:	10,8 vol. %
Ignition temperature:	365 °C DIN 51794
Density (at 20 °C):	0,963 g/cm ³ DIN 51757
Water solubility: (at 20 °C)	virtually insoluble



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 6 of 10

Viscosity / kinematic:
(at 40 °C)

not applicable ASTM D 7042

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable with proper care and handling.

10.2. Chemical stability

The product is chemically stable when handled and stored under normal conditions.

10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

10.5. Incompatible materials

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

10.6. Hazardous decomposition products

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Can be released in case of fire: Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x).
Carbon black.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No data available

Mixture not tested.

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
106-97-8	butane	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	oral	LD50	>5000 mg/kg	Rat.	OECD 401
		dermal	LD50	>5000 mg/kg	Rabbit.	OECD 402
		inhalative (4 h) vapour	LC50	>20 mg/l	Rat.	OECD 403

Irritation and corrosivity

Irritant effect on the eye: Not an irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Sensitising effects

Evaluation: no danger of sensitization.

STOT-single exposure

Vapours may cause drowsiness and dizziness.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 7 of 10

Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information

12.1. Toxicity

No data available

Mixture not tested.

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances
Classified as hazardous waste.

Contaminated packaging

Waste disposal according to official state regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 8 of 10



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)

Quantities released: E0
 Special provisions: 190 - 327 - 625
 Transportation category: 2
 Tunnel restriction code: B1D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L

Other applicable information (inland waterways transport)

Quantities released: E0
 Special provisions: 190 327 625

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: See SP277
 EmS: F-D, S-U

Other applicable information (marine transport)

Quantities released: E0
 Special provisions: 63, 190, 277, 327, 959

Air transport (ICAO)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 9 of 10

14.4. Packing group:

-

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

Other applicable information (air transport)

Passenger LQ: Y203

Quantities released: E0

Danger: Y203

Special provisions: A145 - A153

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 53,6 % (388,064 g/l)

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

- | | |
|-------|---|
| 12 | Extremely flammable. |
| 50 | Very toxic to aquatic organisms. |
| 51 | Toxic to aquatic organisms. |
| 52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| 53 | May cause long-term adverse effects in the aquatic environment. |
| 65 | Harmful: may cause lung damage if swallowed. |
| 66 | Repeated exposure may cause skin dryness or cracking. |

Full text of H statements referred to under Sections 2 and 3

- | | |
|------|---|
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |
| H304 | May be fatal if swallowed and enters airways. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Chain Lube XHT 3000 Spray

Print date: 07.10.2014

Product code: 766028

Page 10 of 10

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)