



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 1 of 9

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

ADDINOL Precision Mechanics Oil XF 12 Spray

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Aerosol.

##### 1.3. Details of the supplier of the safety data sheet

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-201	Telefax: +49 (0) 3461 845-561
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

##### 1.4. Emergency telephone number:

+49 (0) 3461 845-201 - This number is serviced during office hours.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

Indications of danger: F+ - Extremely flammable

R phrases:

Extremely flammable.

###### GHS classification

Hazard categories:

Aerosol: Aerosol 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

##### 2.2. Label elements

Signal word: Danger

Pictograms: GHS02



###### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

###### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 2 of 9

#### Additional advice on labelling

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
203-448-7	butane	35 - 40 %
106-97-8	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1; H220	
265-158-7	Distillates (petroleum), hydrotreated light paraffinic Baseoil - unspecified	35 - 40 %
64742-55-8	Xn - Harmful R65	
	Asp. Tox. 1; H304	
200-827-9	propane	15 - 20 %
74-98-6	F+ - Extremely flammable R12	
601-003-00-5	Flam. Gas 1; H220	
265-077-7	Distillates (petroleum), heavy hydrocracked; Base oil unspecified	5 - 10 %
64741-76-0	Xn - Harmful R65	
	Asp. Tox. 1; H304	
01-2119486951-26		

Full text of R and H phrases: see Section 16.

#### Further Information

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Move victim out of danger zone and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

##### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 3 of 9

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do not induce vomiting.

Rinse mouth thoroughly with water. Immediately get medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

following inhalation: drowsiness. Headache. Nausea.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. Foam.

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Can be released in case of fire: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide. Nitrogen oxides (NO<sub>x</sub>). Carbon black.

Flammable. Vapours may form explosive mixtures with air.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not empty into drains or the aquatic environment.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Guide people to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin, eye and clothing.

#### **6.2. Environmental precautions**

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

#### **6.4. Reference to other sections**

Refer to the provisions listed in Sections 8, 12 and 13.

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 4 of 9

#### Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray into flames or ignition sources. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eye and clothing.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of dampness. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

##### Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

##### Further information on storage conditions

Recommended storage temperature: 10 - 30°C. Do not store at temperatures over: 50°C.

#### 7.3. Specific end use(s)

Further information: refer to Technical Data Sheet.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

##### Additional advice on limit values

source:

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

##### Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

##### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

##### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 5 of 9

Duration of wearing with permanent contact: 480 min  
 Suitable material: NBR (Nitrile rubber).  
 Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min  
 Suitable material: NBR (Nitrile rubber).  
 Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: gaseous  
 Colour: light yellow  
 Odour: like: mineral oil.

#### Test method

#### Changes in the physical state

Initial boiling point and boiling range: < -20 °C  
 Flash point: < -20 °C

#### Explosive properties

evaluation: not Explosive.  
 In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Lower explosion limits: 1,4 vol. %  
 Upper explosion limits: 10,8 vol. %  
 Ignition temperature: 365 °C DIN 51794  
 Vapour pressure: No data available  
 Density (at 20 °C): 0,67 g/cm<sup>3</sup> DIN 51757  
 Viscosity / kinematic: not applicable

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable with proper care and handling.

### 10.2. Chemical stability

The product is chemically stable when handled and stored under normal conditions.

### 10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

### 10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 6 of 9

not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

#### 10.5. Incompatible materials

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

#### 10.6. Hazardous decomposition products

Can be released in case of fire: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide. Nitrogen oxides (NO<sub>x</sub>). Carbon black.

Vapours may form explosive mixtures with air.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

No data available

Mixture not tested.

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
106-97-8	butane				
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified				
	oral	LD50	> 5000 mg/kg	Rat.	
	dermal	LD50	> 2000 mg/kg	Rabbit.	
	inhalative (4 h) vapour	LC50	> 5000 mg/l	Rabbit.	

#### Irritation and corrosivity

Irritant effect on the eye: Not an irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Sensitising effects

Evaluation: no danger of sensitization.

#### Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Carcinogenic/mutagenic/toxic effects for reproduction

No data available

#### Specific effects in experiment on an animal

following inhalation: drowsiness. Headache. Nausea.

#### Additional information on tests

Vapours may cause drowsiness and dizziness. Inhalation causes narcotic effects/intoxication.

#### Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

## SECTION 12: Ecological information

### 12.1. Toxicity

No data available

Mixture not tested.

# Safety Data Sheet

## ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 7 of 9

CAS No	Chemical name	Method	Dose	[h]   [d]	Species	Source
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified					
	Acute fish toxicity	LC50	> 100 mg/l	96 h	Fisch	
	Acute algae toxicity	ErC50	> = 100 mg/l	72 h	Alge	

### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

### 12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

### 12.6. Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

#### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances  
Classified as hazardous waste.

#### Contaminated packaging

Waste disposal according to official state regulations.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1



Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 8 of 9

Transport category: 2  
Tunnel restriction code: D

#### Other applicable information (land transport)

Quantities released: E0  
Special provisions: 190 - 327 - 625  
Transportation category: 2  
Tunnel restriction code: B1D

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L

#### Other applicable information (inland waterways transport)

Quantities released: E0  
Special provisions: 190 327 625

#### Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: See SP277  
EmS: F-D, S-U

#### Other applicable information (marine transport)

Quantities released: E0  
Special provisions: 63, 190, 277, 327, 959

#### Air transport (ICAO)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1





## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Print date: 07.10.2014

Product code: 774000

Page 9 of 9

Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

#### Other applicable information (air transport)

Passenger LQ: Y203  
 Quantities released: E0  
 Danger: Y203  
 Special provisions: A145 - A153

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

Warning: Flammable gases.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

1999/13/EC (VOC): 56,8 % (380,56 g/l)

##### National regulatory information

Employment restrictions: Observe employment restrictions for young people.  
 Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Full text of R phrases referred to under Sections 2 and 3

12 Extremely flammable.  
 65 Harmful: may cause lung damage if swallowed.

#### Full text of H statements referred to under Sections 2 and 3

H220 Extremely flammable gas.  
 H222 Extremely flammable aerosol.  
 H229 Pressurised container: May burst if heated.  
 H304 May be fatal if swallowed and enters airways.

#### Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*