

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 1 of 9

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

ADDINOL Precision Mechanics Oil XF 12 Spray

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Aerosol.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0	Telefax: +49 (0) 3461 845-555
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

##### Supplier

Company name:	Specialised Products (Western) Limited	
Street:	76 Cobham Road, Ferndown Industrial Estate,	
Place:	GB-BH21 7RN Wimborne, Dorset	
Telephone:	+44 1202 891393	Telefax: +44 1202 876908
e-mail:	sales@specialisedproducts.co.uk	
Internet:	http://specialisedproducts.co.uk	

#### 1.4. Emergency telephone number:

+44 1202 891393 - This number is serviced during office hours.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



##### Hazard statements

H222 Extremely flammable aerosol.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 2 of 9

H229 Pressurised container: May burst if heated.

### Precautionary statements

P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container to an appropriate recycling or disposal facility.

### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
106-97-8	butane			35 - 40 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic Baseoil - unspecified			35 - 40 %
	265-158-7		01-2119487077-29	
	Asp. Tox. 1; H304			
74-98-6	propane			15 - 20 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

#### Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 3 of 9

case of skin irritation, seek medical treatment.

### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. Foam.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide Nitrogen oxides (NO<sub>x</sub>). carbon black.

Flammable.. Vapours may form explosive mixtures with air.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin, eye and clothing.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 4 of 9

cellars, flues and ditches. Avoid contact with skin, eye and clothing.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

##### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

##### Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

#### 7.3. Specific end use(s)

Further information: see technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### Additional advice on limit values

source:

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 5 of 9

Wearing time with occasional contact (splashes): 30 min  
 Suitable material: NBR (Nitrile rubber).  
 Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	gaseous
Colour:	light yellow
Odour:	like: mineral oil.

#### Test method

pH-Value:	No data available
-----------	-------------------

#### Changes in the physical state

Melting point:	No data available
Initial boiling point and boiling range:	< -20 °C
Flash point:	< -20 °C

#### Flammability

Solid:	No data available
Gas:	No data available

#### Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Lower explosion limits:	3 vol. %
Upper explosion limits:	15 vol. %
Ignition temperature:	365 °C DIN 51794

#### Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	No data available
----------------------------	-------------------

#### Oxidizing properties

No data available

Vapour pressure:	No data available
------------------	-------------------

Density (at 20 °C):	0,66 g/cm <sup>3</sup> DIN 51757
---------------------	----------------------------------

Water solubility:	virtually insoluble
-------------------	---------------------

#### Solubility in other solvents

not determined

Partition coefficient:	No data available
------------------------	-------------------

Viscosity / kinematic:	not applicable
------------------------	----------------

Vapour density:	not determined
-----------------	----------------

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 6 of 9

Evaporation rate: not determined

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

### 10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

### 10.5. Incompatible materials

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide Nitrogen oxides (NO<sub>x</sub>). carbon black.

Vapours may form explosive mixtures with air.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### **Acute toxicity**

Based on available data, the classification criteria are not met.  
Mixture not tested.

#### **Irritation and corrosivity**

Based on available data, the classification criteria are not met.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.  
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Specific effects in experiment on an animal**

following inhalation: drowsiness. Headache. Nausea.

#### **Additional information on tests**

Vapours may cause drowsiness and dizziness. Inhalation causes narcotic effects/intoxication.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 7 of 9

**Further information**

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

#### SECTION 12: Ecological information

**12.1. Toxicity**

No data available

Mixture not tested.

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

**12.4. Mobility in soil**

Product is easily volatile. Product is difficult to dissolve in water.

**12.5. Results of PBT and vPvB assessment**

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

**12.6. Other adverse effects**

No data available

#### SECTION 13: Disposal considerations

**13.1. Waste treatment methods****Advice on disposal**

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**Contaminated packaging**

Dispose of waste according to applicable legislation.

#### SECTION 14: Transport information

**Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1



Classification code: 5F

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 8 of 9

Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Precision Mechanics Oil XF 12 Spray

Revision date: 20.06.2019

Product code: 77400028

Page 9 of 9

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

Warning: flammable gases.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Distillates (petroleum), hydrotreated light paraffinic Baseoil - unspecified

Entry 28a: butane

2010/75/EU (VOC): 56,488 % (372,819 g/L)

2004/42/EC (VOC): 56,772 % (374,693 g/L)

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

##### Additional information

Please note: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC, Aerosol directive (75/324/EEC)

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,5,7,8,9,10,11,12,15,16.

#### Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.  
 H222 Extremely flammable aerosol.  
 H229 Pressurised container: May burst if heated.  
 H304 May be fatal if swallowed and enters airways.

#### Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*