

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 150 MW**

Revision date: 12.12.2022

Product code: 741062

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

ADDINOL Gear Oil CLP 150 MW

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Gearbox oil.

For industrial purposes only.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0	Telefax: +49 (0) 3461 845-555
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

**Supplier**

Company name:	Specialised Products (Western) Limited	
Street:	76 Cobham Road, Ferndown Industrial Estate	
Place:	GB-BH21 7RN Wimborne, Dorset	
Telephone:	+44 1202 891393	Telefax: +44 1202 876908
e-mail:	sales@specialisedproducts.co.uk	
Internet:	http://specialisedproducts.co.uk	

**1.4. Emergency telephone number:**

+44 1202 891393 - This number is serviced during office hours.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

**2.2. Label elements****GB CLP Regulation****Special labelling of certain mixtures**

EUH208	Contains Di-tert-butyl-Polysulfides, Amines, C10-C14-tert-alkyl. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

**Additional advice on labelling**

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
Spilled product must not leak into the ground.  
Do not allow uncontrolled leakage of product into the environment.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Gear Oil CLP 150 MW

Revision date: 12.12.2022

Product code: 741062

Page 2 of 12

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			40 - < 50 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
68937-96-2	Di-tert-butyl-Polysulfides			0.5 - < 1 %
	273-103-3		01-2119540515-43	
	Skin Sens. 1, Aquatic Chronic 3; H317 H412			
68955-53-3	Amines, C10-C14-tert-alkyl			< 0.1 %
	701-175-2		01-2119456798-18	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H318 H317 H400 H410			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	40 - < 50 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
68955-53-3	701-175-2	Amines, C10-C14-tert-alkyl	< 0.1 %
	inhalation: LC50 = >= 157 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = > 500 mg/kg M acute; H400: M=1 M chron.; H410: M=1		

### Further Information

The product does not contain any dangerous substances with concentrations reaching or exceeding the limits acc. to 1272/2008 [GHS].

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Gear Oil CLP 150 MW

Revision date: 12.12.2022

Product code: 741062

Page 3 of 12

Rinse mouth thoroughly with water. Call a physician immediately.

### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

### **4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

#### **Unsuitable extinguishing media**

High power water jet.

### **5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. carbon black.

### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## SECTION 6: Accidental release measures

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### **6.3. Methods and material for containment and cleaning up**

#### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## SECTION 7: Handling and storage

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Gear Oil CLP 150 MW

Revision date: 12.12.2022

Product code: 741062

Page 4 of 12

### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.  
Keep away from: Oxidizing agents.

#### Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.  
Recommended storage temperature: 5 - 40°C

### 7.3. Specific end use(s)

Further information: see technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
68937-96-2	Di-tert-butyl-Polysulfides			
Worker DNEL, long-term		inhalation	systemic	3,29 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	4,67 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,58 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	1,67 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,167 mg/kg bw/day
68955-53-3	Amines, C10-C14-tert-alkyl			
Worker DNEL, long-term		inhalation	systemic	12,5 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	12,1 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	1,2 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	0,35 mg/kg bw/day

## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Gear Oil CLP 150 MW

Revision date: 12.12.2022

Product code: 741062

Page 5 of 12

#### PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
68937-96-2	Di-tert-butyl-Polysulfides	
Freshwater		0,00024 mg/l
Freshwater (intermittent releases)		0,002 mg/l
Marine water		0,000024 mg/l
Freshwater sediment		0,94 mg/kg
Marine sediment		0,094 mg/kg
Secondary poisoning		6,66 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,51 mg/l
Soil		0,0181 mg/kg
68955-53-3	Amines, C10-C14-tert-alkyl	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,004 mg/l
Marine water		0 mg/l
Freshwater sediment		2,14 mg/kg
Marine sediment		0,214 mg/kg
Secondary poisoning		4,71 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,635 mg/l
Soil		0,428 mg/kg

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

##### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 150 MW**

Revision date: 12.12.2022

Product code: 741062

Page 6 of 12

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

**Skin protection**

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point &gt; 65°C: A1: &lt; 1000 ppm; A2: &lt; 5000 ppm; A3: &lt; 10000 ppm

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow - brown
Odour:	like: mineral oil.
Odour threshold:	not determined

**Test method****Changes in the physical state**

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	not determined
Pour point:	-28 °C ASTM D 7346
Flash point:	> 220 °C DIN EN ISO 2592

**Flammability**

Solid/liquid:	No data available
Gas:	No data available

**Explosive properties**

No data available

Lower explosion limits:	No data available
Upper explosion limits:	No data available
Auto-ignition temperature:	not determined

**Self-ignition temperature**

Solid:	No data available
Gas:	No data available

Decomposition temperature: No data available

pH-Value: not applicable

Viscosity / kinematic: 150 mm<sup>2</sup>/s ASTM D 7042  
(at 40 °C)

Water solubility: virtually insoluble

**Solubility in other solvents**

No data available

Partition coefficient n-octanol/water: No data available

Vapour pressure: No data available

Density (at 15 °C): 0,895 g/cm<sup>3</sup> DIN 51757

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Gear Oil CLP 150 MW

Revision date: 12.12.2022

Product code: 741062

Page 7 of 12

Relative vapour density:

No data available

### **9.2. Other information**

#### **Information with regard to physical hazard classes**

Oxidizing properties

No data available

#### **Other safety characteristics**

Evaporation rate:

No data available

#### **Further Information**

No data available

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

### **10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### **10.3. Possibility of hazardous reactions**

No known hazardous reactions.

### **10.4. Conditions to avoid**

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

### **10.5. Incompatible materials**

Reacts with: Oxidizing agents, strong. Acid.

### **10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. carbon black.

## **SECTION 11: Toxicological information**

### **11.1. Information on hazard classes as defined in GB CLP Regulation**

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 150 MW**

Revision date: 12.12.2022

Product code: 741062

Page 8 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982) OECD Guideline 401
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982) OECD Guideline 402
68955-53-3	Amines, C10-C14-tert-alkyl				
	oral	LD50 mg/kg	> 500	Rat	Study report (1993) OECD Guideline 401
	dermal	LD50 mg/kg	251	Rat	Study report (1993) OECD Guideline 402
	inhalation (4 h) vapour	LC50 mg/l	>= 157	Rat	Study report (2001) OECD Guideline 403
	inhalation dust/mist	ATE	0,05 mg/l		

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Sensitising effects**

Contains Di-tert-butyl-Polysulfides, Amines, C10-C14-tert-alkyl. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable

**SECTION 12: Ecological information****12.1. Toxicity**

No data available

Mixture not tested.



**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 150 MW**

Revision date: 12.12.2022

Product code: 741062

Page 9 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h			
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
68937-96-2	Di-tert-butyl-Polysulfides					
	Acute algae toxicity	ErC50 0,838 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 63 mg/l	48 h	Daphnia magna	Study report (2013)	OECD Guideline 202
68955-53-3	Amines, C10-C14-tert-alkyl					
	Acute fish toxicity	LC50 1,3 mg/l	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 0,44 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)	OECD Guideline 201
	Acute crustacea toxicity	EC50 4,1 mg/l	48 h	Daphnia magna	Study report (1984)	OECD Guideline 202
	Fish toxicity	NOEC 0,078 mg/l	96 d	Oncorhynchus mykiss	Study report (2002)	OECD Guideline 210
	Acute bacteria toxicity	(EC50 63,5 mg/l)	0,5 h	activated sludge of a predominantly domestic sewage	Study report (2008)	OECD Guideline 209

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
68937-96-2	Di-tert-butyl-Polysulfides	5,6
68955-53-3	Amines, C10-C14-tert-alkyl	2,9

**BCF**

CAS No	Chemical name	BCF	Species	Source
68937-96-2	Di-tert-butyl-Polysulfides	0,006	Lepomis macrochirus	Study report (2015)

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 150 MW**

Revision date: 12.12.2022

Product code: 741062

Page 10 of 12

**Further information**

Do not allow uncontrolled leakage of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**List of Wastes Code - residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

**SECTION 14: Transport information****Land transport (ADR/RID)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

**Inland waterways transport (ADN)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

**Marine transport (IMDG)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

**Air transport (ICAO-TI/IATA-DGR)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**Other applicable information**

No dangerous good in sense of these transport regulations.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 150 MW**

Revision date: 12.12.2022

Product code: 741062

Page 11 of 12

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,4,6,7,9,11,12,16.

**Abbreviations and acronyms**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Relevant H and EUH statements (number and full text)**

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Di-tert-butyl-Polysulfides, Amines, C10-C14-tert-alkyl. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

**Further Information**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Gear Oil CLP 150 MW**

Revision date: 12.12.2022

Product code: 741062

Page 12 of 12

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*