

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

ADDINOL Gas Engine Oil LG 40

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Motor oil.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: ADDINOL Lube Oil GmbH
Gebäude 4609
Street: Am Haupttor
Place: D-06237 Leuna
Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555
e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de
Responsible Department: ADDINOL Application Technology

Supplier

Company name: Gidov Oil & Logistics Ltd.
Street: 76 Cobham Road, Ferndown Industrial Estate
Place: GB-TN157DA Wrotham, Sevenoaks Kent
Telephone: +44 7729229830 Telefax: +44 7729229830
e-mail: sales@addinol.co.uk
Internet: https://www.gidovlogistics.co.uk/

1.4. Emergency telephone number: +44 7729229830 - This number is serviced during office hours.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

Precautionary statementsP273 Avoid release to the environment.
P501 Dispose of contents/container to industrial incineration plant.**Special labelling of certain mixtures**

EUH208 Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May produce an allergic reaction.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 2 of 12

2.3. Other hazards

- Endocrine disrupting properties: phenol, dodecyl-, branched.
- Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
- Spilled product must not leak into the ground.
- Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			80 - < 100 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts			0.5 - < 1 %
	274-263-7		01-2119492616-28	
	Skin Sens. 1B; H317			
121158-58-5	phenol, dodecyl-, branched			0.1 - < 0.3 %
	310-154-3	604-092-00-9	01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	80 - < 100 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
70024-69-0	274-263-7	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	0.5 - < 1 %
	dermal: LD50 = > 4000 mg/kg; oral: LD50 = > 16000 mg/kg		
121158-58-5	310-154-3	phenol, dodecyl-, branched	0.1 - < 0.3 %
	dermal: LD50 = ca. 15000 mg/kg; oral: LD50 = 2100 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 3 of 12

case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Nitrogen oxides (NO_x). Hydrogen sulphide (H₂S). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 4 of 12

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 5 of 12

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts		
Worker DNEL, long-term	inhalation	systemic	11,75 mg/m ³
Worker DNEL, long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term	dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term	dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	0,513 mg/cm ²
Consumer DNEL, long-term	oral	systemic	0,833 mg/kg bw/day
121158-58-5	phenol, dodecyl-, branched		
Worker DNEL, acute	inhalation	systemic	44,18 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	166 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,79 mg/m ³
Consumer DNEL, acute	inhalation	systemic	13,26 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	1,26 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 6 of 12

PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg
121158-58-5	phenol, dodecyl-, branched	
Freshwater		0,000074 mg/l
Freshwater (intermittent releases)		0,00037 mg/l
Marine water		0,000007 mg/l
Freshwater sediment		0,226 mg/kg
Marine sediment		0,027 mg/kg
Secondary poisoning		4 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,118 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³STEL: 10 mg/m³

Does not contain substances above concentration limits fixing an occupational exposure limit.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 7 of 12

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	brown - black
Odour:	like: mineral oil.
Odour threshold:	not determined

	Test method
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	270 °C DIN EN ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 100 °C)	13,6 mm ² /s ASTM D 7042
Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,872 g/cm ³ DIN 51757
Relative vapour density:	No data available

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Pour point:

-32 °C ASTM D 7346

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 8 of 12

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Nitrogen oxides (NO_x). Hydrogen sulphide (H₂S). carbon black. No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts				
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)	other: 40 CFR, Section 163.81-2, Federal
121158-58-5	phenol, dodecyl-, branched				
	oral	LD50 2100 mg/kg	Rat	Publication (1978)	OECD Guideline 401
	dermal	LD50 ca. 15000 mg/kg	Rabbit	Study report (1968)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 9 of 12

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting properties: phenol, dodecyl-, branched.
not applicable

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h			
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts					
	Acute fish toxicity	LL50 > 10000 mg/l	96 h	Cyprinodon variegatus	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	EPA OTS 797.1050
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Acute bacteria toxicity	(EC50 > 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier	OECD Guideline 209
121158-58-5	phenol, dodecyl-, branched					
	Acute fish toxicity	LL50 40 mg/l	96 h	Pimephales promelas	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 0,15 mg/l	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,037 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,004 mg/l	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 > 1000 mg/l)	3 h	activated sludge of a predominantly industrial sew	Study report (2004)	OECD Guideline 209

12.2. Persistence and degradability

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 10 of 12

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	18,05
121158-58-5	phenol, dodecyl-, branched	7,14

BCF

CAS No	Chemical name	BCF	Species	Source
121158-58-5	phenol, dodecyl-, branched	289	Oncorhynchus mykiss	Study report (2006)

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

Endocrine disrupting properties: phenol, dodecyl-, branched.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 11 of 12

14.2. UN proper shipping name: -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

phenol, dodecyl-, branched

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,5,6,7,8,9,10,12,15,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gas Engine Oil LG 40

Revision date: 24.08.2023

Product code: 725018

Page 12 of 12

Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May produce an allergic reaction.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)