according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024	Product code: 717302	Page 1 of 14	
SECTION 1: Identification of the s	ubstance/mixture and of the company/un	dertaking	
1.1. Product identifier			
ADDINOL Electro Contact Spra	у		
UFI:	GVNT-ENPU-NN0R-25KF		
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised against		
Use of the substance/mixture			
Aerosols - Cleaning agent			
1.3. Details of the supplier of the safe	ty data sheet		
Manufacturer			
Company name:	ADDINOL Lube Oil GmbH		
	Gebäude 4609		
Street:	Am Haupttor		
Place:	D-06237 Leuna		
Telephone:	+49 (0) 3461 845-0	Telefax: +49 (0) 3461 845-555	
E-mail:	info@addinol.de		
Contact person:	Application Technology		
Internet:	www.addinol.de		
Responsible Department:	ADDINOL Application Technology		
Supplier			
Company name:	Gidov Oil & Logistics Ltd.		
Street:	76 Cobham Road, Ferndown Industrial Estate		
Place:	GB-TN157DA Wrotham, Sevenoaks Kent		
Telephone:	+44 7729229830	Telefax:+44 7729229830	
E-mail:	sales@addinol.co.uk		
Internet:	https://www.gidovlogistics.co.uk/		
1.4. Emergency telephone	+44 7729229830 - This number is serviced du	ring office hours.	

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Asp. Tox. 1; H304 Aquatic Chronic 4; H413

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

2.2. Label elements

GB CLP Regulation Signal word:

Pictograms:



Danger

Hazard statements H222

H229

Extremely flammable aerosol. Pressurised container: May burst if heated.

according to UK REACH Regulation

ADDINOL Electro Contact Spray									
Revision date: 11.07.2024	Product code: 717302	Page 2 of 14							
H413	May cause long lasting harmful effects to aquatic life.								
Precautionary statemer	Precautionary statements								
P102	Keep out of reach of children.								
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.								
P211	Do not spray on an open flame or other ignition source.								
P251	Do not pierce or burn, even after use.								
P273	Avoid release to the environment.								
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.								
P501	Dispose of contents/container to industrial incineration plant.								
Special labelling of cert	tain mixtures								
EUH066	Repeated exposure may cause skin dryness or cracking. 92 % by mass of the contents are flammable.								
Additional advice on la	belling								

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Chemical name					
	EC No	Index No	REACH No				
	Classification (GB CLP Regulation))	•				
	Hydrocarbons, C11-C12, isoalkane		60 - < 80 %				
	918-167-1		01-2119472146-39				
	Flam. Liq. 3, Asp. Tox. 1, Aquatic 0	3					
106-97-8	butane		10 - < 20 %				
	203-448-7	203-448-7 601-004-00-0					
	Flam. Gas 1, Liquefied gas; H220 I	H280					
74-98-6	propane		5 - < 10 %				
	200-827-9	601-003-00-5					
	Flam. Gas 1, Liquefied gas; H220 I						
8042-47-5	White mineral oil		2.5 - < 5 %				
	232-455-8		01-2119487078-27				
	Asp. Tox. 1; H304						

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc. Limits, M-factors and ATE					
	918-167-1	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	60 - < 80 %			
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg					
8042-47-5	232-455-8	White mineral oil	2.5 - < 5 %			
dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg						

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024

Product code: 717302

Page 3 of 14

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water. High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Flammable. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024

Product code: 717302

Page 4 of 14

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers). Explosion risk.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory) Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting. Do not pierce or burn, even after use.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Further information on handling

People who suffer from asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024

Product code: 717302

Page 5 of 14

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance							
DNEL type		Exposure route	Effect	Value				
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics								
Worker DNEI	L, long-term	inhalation	systemic	7 mg/m³				
Worker DNEI	L, long-term	dermal	systemic	4 mg/kg bw/day				
Consumer DI	NEL, long-term	inhalation	systemic	1,7 mg/m³				
Consumer DI	NEL, long-term	dermal	systemic	2 mg/kg bw/day				
Consumer DI	NEL, long-term	oral	systemic	0,5 mg/kg bw/day				
8042-47-5	White mineral oil							
Worker DNEI	L, long-term	dermal	systemic	217,05 mg/kg bw/day				
Worker DNEI	L, long-term	inhalation	systemic	164,56 mg/m ³				
Consumer DNEL, long-term		dermal	systemic	93,02 mg/kg bw/day				
Consumer DI	NEL, long-term	inhalation	systemic	34,78 mg/m ³				
Consumer DI	NEL, long-term	oral	systemic	25 mg/kg bw/day				

PNEC values

CAS No	Substance					
Environment	Environmental compartment					
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics						
Freshwater 0,026 mg/l						
Freshwater (intermittent releases) 0,263						
Marine water	·	0,003 mg/l				
Freshwater s	sediment	0,344 mg/kg				
Marine sedin	nent	0,034 mg/kg				
Micro-organi	sms in sewage treatment plants (STP)	100 mg/l				
Soil		0,053 mg/kg				

Additional advice on limit values

source:

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024

Product code: 717302

Page 6 of 14

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets. Wear anti-static footwear and clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65° C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold:	gaseous light yellow odourless not determined		
			Test method
Melting point/freezing point:		not applicable	
Boiling point or initial boiling point and		< -20 °C	
boiling range:			
Flammability:		not applicable	
Lower explosion limits:		0,6 vol. %	
Upper explosion limits:		10,9 vol. %	
Flash point:		< -20 °C	DIN EN ISO 2592
Auto-ignition temperature:		>200 °C	DIN 51794
Decomposition temperature:		not determined	
pH-Value:		not applicable	
Viscosity / kinematic:		not applicable	
Water solubility:		insoluble	
(at 20 °C)			
Solubility in other solvents			
No data available			
Partition coefficient n-octanol/water:		not determined	
Vapour pressure:		not determined	
(at 20 °C)		/	
Density (at 20 °C):		0,765 g/cm ³	DIN 51757
Relative vapour density:		No data available	
Particle characteristics:		No data available	

according to UK REACH Regulation

ADDINOL	Electro	Contact	Spray
---------	---------	---------	-------

Revision date: 11.07.2024

Product code: 717302

Page 7 of 14

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Self-ignition temperature	U	•	0,	
Solid:				not applicable
Gas:				not applicable
Oxidizing properties				
No data available				
Other safety characteristics				
Evaporation rate:				not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

10.5. Incompatible materials

Keep away from: Oxidising agent, strong

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Vapours may form explosive mixtures with air.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024

Product code: 717302

Page 8 of 14

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics								
	oral LD50 > 5000 Rat Study report (1995) OECD Gui								
	dermal	LD50 > mg/kg	2000	Rat	Study report (2016)	OECD Guideline 402			
8042-47-5	White mineral oil								
	oral	LD50 > mg/kg	5000	Rat	Study report (1987)	OECD Guideline 401			
	dermal	LD50 > mg/kg	2000	Rabbit	Study report (1987)	OECD Guideline 402			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information

12.1. Toxicity

May cause long lasting harmful effects to aquatic life.

according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024

Product code: 717302

Page 9 of 14

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
	Hydrocarbons, C11-C12,	isoalkanes,	<2% aromat	ics					
	Acute fish toxicity	LC50 mg/l	26,3	96 h	Oncorhynchus mykiss	REACh Registration Dossier	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	> 59,6	72 h	Raphidocelis subcapitata	REACh Registration Dossier	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	84,91	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202		
	Fish toxicity	NOEC mg/l	>= 100	32 d	Pimephales promelas	REACh Registration Dossier	OECD Guideline 210		
	Crustacea toxicity	NOEC	> 1 mg/l	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211		
	Acute bacteria toxicity	EC50 mg/l()	> 1000	3 h	activated sludge of a predominantly domestic sewag	REACh Registration Dossier	OECD Guideline 209		
106-97-8	butane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
74-98-6	propane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
8042-47-5	White mineral oil								
	Acute fish toxicity	LL50 mg/l	> 10000	96 h	Leuciscus idus melanotus	Study report (1992)	OECD Guideline 203		
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024

Product code: 717302

Page 10 of 14

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	1,15
106-97-8	butane	1,09
74-98-6	propane	1,09

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	>= 6,91	calculated	REACh Registration D

12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2

according to UK REACH Regulation

Revision date: 11.07.2024	ADDINOL Electro Contact Spray Product code: 717302	Page 11 of 14
Tunnel restriction code:	D	
nland waterways transport (ADN)		
14.1. UN number or ID number:	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2	
14.4. Packing group:	-	
Hazard label:	2.1	
Classification code:	5F	
Special Provisions:	190 327 344 625	
Limited quantity:	1L	
Excepted quantity:	E0	
Marine transport (IMDG)		
14.1. UN number or ID number:	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Special Provisions:	63, 190, 277, 327, 344, 959	
Limited quantity:	1000 mL	
Excepted quantity: EmS:	E0 F-D, S-U	
	1-0, 3-0	
Air transport (ICAO-TI/IATA-DGR)	UN 1950	
<u>14.1. UN number or ID number:</u> 14.2. UN proper shipping name:	AEROSOLS, flammable	
14.2. ON proper snipping name. 14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	2.1	
Hazard label:	2.1	
Special Provisions:	A145 A167 A802	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:	203	
IATA-max. quantity - Passenger:	75 kg	
IATA-packing instructions - Cargo:	203	
IATA-max. quantity - Cargo:	150 kg	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user		
Warning: flammable gases.		
14.7. Maritime transport in bulk according	o IMO instruments	
not applicable		

according to UK REACH Regulation

ADDINOL	Electro	Contact	Spray
---------	---------	---------	-------

Revision date: 11.07.2024

Product code: 717302

Page 12 of 14

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information		
Restrictions on use (REACH, annex XVII): Entry 28, Entry 40		
Directive 2010/75/EU on industrial emissions:	96,5% (661,025 g/L)	
Directive 2004/42/EC on VOC in paints and varnishes:	96,5% (661,025 g/L)	
Information according to Directive 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS	
Additional information		
To follow: Aerosolrichtlinie (75/324/EW0	G)	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).	
Water hazard class (D):	1 - slightly hazardous to water	
15.2. Chemical safety assessment		
Chemical safety assessments for substances in this mixture were not carried out.		

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2.

according to UK REACH Regulation

ADDINOL	Electro	Contact	Spray
---------	---------	---------	-------

Revision date: 11.07.2024

Product code: 717302

Page 13 of 14

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: RID -Regulation concerning the International Carriage of Dangerous Goods by Rail: RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification	Classification procedure
Aerosol 1; H222-H229	
Asp. Tox. 1; H304	
Aquatic Chronic 4; H413	Calculation method

Classification for mixtures and used evaluation method according to GB CLP Regulation

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of

according to UK REACH Regulation

ADDINOL Electro Contact Spray

Revision date: 11.07.2024

Product code: 717302

Page 14 of 14

processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)