according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 1 of 19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Penta-Cool WM 650

Product group: Zulieferprodukt

UFI: J19G-8W20-V47N-04K3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Metal working fluids.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

E-mail: info@addinol.de
Contact person: Application Technology

Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Gidov Oil & Logistics Ltd.

Street: 76 Cobham Road, Ferndown Industrial Estate
Place: GB-TN157DA Wrotham, Sevenoaks Kent

Telephone: +44 7729229830 Telefax: +44 7729229830

E-mail: sales@addinol.co.uk

Internet: https://www.gidovlogistics.co.uk/

1.4. Emergency telephone +44 7729229830 - This number is serviced during office hours.

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

2-phenoxyethanol

 $1,2\text{-benzisothiazol-}3(2H)\text{-one};\ 1,2\text{-benzisothiazolin-}3\text{-one}$ octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]

2-methylisothiazol-3(2H)-one **Signal word:** Danger

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 2 of 19

Pictograms:





Hazard statements

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P310 Immediately call a POISON CENTER/doctor.
P333+P317 If skin irritation or rash occurs: Get medical help.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 3 of 19

Relevant ingredients

CAS No	Chemical name	Quantity				
	EC No	Index No	REACH No			
	Classification (GB CLP Re	egulation)	·			
122-99-6	2-phenoxyethanol			5 - < 10 %		
	204-589-7	603-098-00-9				
	Acute Tox. 4, Eye Dam. 1	STOT SE 3; H302 H318 H335	·			
68608-26-4	Sodium sulphonate			1 - < 5 %		
	271-781-5					
	Eye Irrit. 2; H319	•	·			
68920-66-1	Alcohols, C16-18 and C18	-unsatd., ethoxylated		2.5 - < 5 %		
	500-236-9		01-2119489407-26			
	Skin Irrit. 2, Aquatic Chror	ic 2; H315 H411	·			
112-34-5	2-(2-butoxyethoxy)ethano	< 5 %				
	203-961-6	603-096-00-8				
	Eye Irrit. 2; H319	-				
2634-33-5	1,2-benzisothiazol-3(2H)-	< 0,25 %				
	220-120-9	613-088-00-6				
	Acute Tox. 4, Skin Irrit. 2, H400					
26530-20-1	octhilinone (ISO); 2-octyl-2	< 0,025 %				
	247-761-7	613-112-00-5				
	Acute Tox. 2, Acute Tox. 3 1, Aquatic Chronic 1; H33					
2682-20-4	2-methylisothiazol-3(2H)-c	< 0,05 %				
	220-239-6	613-326-00-9				
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H301 H314 H318 H317 H400 H410 EUH071					

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 4 of 19

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity					
	Specific Conc.	Limits, M-factors and ATE						
122-99-6	204-589-7	2-phenoxyethanol	5 - < 10 %					
	dermal: LD50	= >2000 mg/kg; oral: ATE 1394 mg/kg						
68608-26-4	271-781-5	Sodium sulphonate	1 - < 5 %					
	dermal: LD50	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg						
68920-66-1	20-66-1 500-236-9 Alcohols, C16-18 and C18-unsatd., ethoxylated							
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = > 2000 mg/kg						
112-34-5	203-961-6	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	< 5 %					
	dermal: LD50 = 4120 mg/kg; oral: LD50 = 5660 mg/kg							
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	< 0,25 %					
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = 670 mg/kg						
26530-20-1	247-761-7	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]	< 0,025 %					
	Skin Sens. 1A; Aquatic Acute	E 0,27 mg/l (dusts or mists); dermal: ATE 311 mg/kg; oral: ATE 125 mg/kg H317: >= 0,0015 - 100 1; H400: M=100 c 1; H410: M=100						
2682-20-4	220-239-6	2-methylisothiazol-3(2H)-one	< 0,05 %					
	= 242 mg/kg; o Aquatic Acute	E = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 ral: LD50 = 120 mg/kg						

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Protect skin by using skin protective cream. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 5 of 19

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Sand. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Sulphur dioxide (SO2).. Nitrogen oxides (NOx). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 6 of 19

Keep away from: Oxidizing agent.

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat. Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 7 of 19

DNEL/DMEL values

Exposure route	CAS No	Substance			
	DNEL type	•	Exposure route	Effect	Value
Consumer DNEL, long-term	122-99-6	2-phenoxyethanol			
Consumer DNEL, long-term inhalation local 2,41 mg/m² Consumer DNEL, long-term dermal systemic 10.42 mg/kg bw/day Consumer DNEL, long-term oral systemic 9.23 mg/kg bw/day Consumer DNEL, acute oral systemic 9.23 mg/kg bw/day Worker DNEL, long-term dermal systemic 9.23 mg/kg bw/day Worker DNEL, long-term inhalation systemic 5.7 mg/m³ 86809-26-4 Sodium sulphonate systemic 0.96 mg/m³ Worker DNEL, long-term inhalation systemic 9.33 mg/kg bw/day Worker DNEL, long-term dermal systemic 0.33 mg/kg bw/day Consumer DNEL, long-term dermal systemic 0.33 mg/kg bw/day Consumer DNEL, long-term oral systemic 0.33 mg/kg bw/day 68920-66-1 Alcohols, C16-18 and C18-unsatd., ethoxylated Consumer DNEL, long-term inhalation systemic 87 mg/m² Consumer DNEL, long-term dermal systemic 25 mg/kg bw/day Worker DNEL, long-term dermal systemic<	Worker DNEL	, long-term	inhalation	local	5,7 mg/m³
Consumer DNEL, long-term	Consumer DN	IEL, long-term	inhalation	systemic	2,41 mg/m³
Consumer DNEL, long-term oral systemic 9,23 mg/kg bw/day Consumer DNEL, long-term dermal systemic 9,23 mg/kg bw/day Worker DNEL, long-term dermal systemic 20,83 mg/kg bw/day Worker DNEL, long-term inhalation systemic 5,7 mg/m² 88603-26-4 Sodium sulphonate Worker DNEL, long-term dermal systemic 0,66 mg/m² Worker DNEL, long-term dermal systemic 3,333 mg/kg bw/day Worker DNEL, long-term dermal systemic 3,333 mg/kg bw/day Consumer DNEL, long-term dermal systemic 3,333 mg/kg bw/day Consumer DNEL, long-term dermal systemic 0,33 mg/m² Consumer DNEL, long-term dermal systemic 3,338 mg/kg bw/day Consumer DNEL, long-term oral systemic 87 mg/m² S68920-66-1 Alcohols, C16-18 and C18-unsatid., ethoxylated Consumer DNEL, long-term dermal systemic 87 mg/m² Consumer DNEL, long-term oral systemic 87 mg/m² Consumer DNEL, long-term dermal systemic 250 mg/kg bw/day Worker DNEL, long-term dermal systemic 2008 mg/kg bw/day Worker DNEL, long-term inhalation systemic 226 mg/kg bw/day Worker DNEL, long-term inhalation local 67,5 mg/m² 112-34-5 2-(2-buloxyethoxy)ethanol; diethylene glycol monobulyl ether Worker DNEL, long-term inhalation local 67,5 mg/m² Worker DNEL, long-term inhalation systemic 9,268 mg/kg bw/day Worker DNEL, long-term inhalation local 67,5 mg/m² Worker DNEL, long-term inhalation systemic 6,81 mg/m² 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,345 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,345 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,345 mg/kg bw/day Consumer DNEL, long-term inhalation local 0,021 mg/m² Consumer DNEL, long-term inhalation systemic 0,345 mg/kg bw/day	Consumer DN	IEL, long-term	inhalation	local	2,41 mg/m³
Switch S	Consumer DN	EL, long-term	dermal	systemic	
Worker DNEL, ong-term dermal systemic 20,83 mg/kg bw/day worker DNEL, ong-term inhalation systemic 5,7 mg/m³ 686608-26-4 Sodium sulphonate	Consumer DN	EL, long-term	oral	systemic	
bw/day	Consumer DN	EL, acute	oral	systemic	
68608-26-4 Sodium sulphonate Worker DNEL, long-term inhalation systemic 0,66 mg/m² Worker DNEL, long-term dermal systemic 3,33 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,33 mg/m² Consumer DNEL, long-term dermal systemic 1,667 mg/kg bw/day Consumer DNEL, long-term oral systemic 0,833 mg/kg bw/day 68920-66-1 Alcohols, C16-18 and C18-unsatd., ethoxylated 87 mg/m² 87 mg/m² Consumer DNEL, long-term inhalation systemic 87 mg/m² Consumer DNEL, long-term dermal systemic 25 mg/kg bw/day Worker DNEL, long-term dermal systemic 25 mg/kg bw/day Worker DNEL, long-term dermal systemic 294 mg/m² 112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether worker DNEL, long-term inhalation local 67,5 mg/m² Worker DNEL, long-term inhalation local 67,5 mg/m² 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-	Worker DNEL	, long-term	dermal	systemic	
Worker DNEL, long-term inhalation systemic 0,66 mg/m³ Worker DNEL, long-term dermal systemic 3,33 mg/kg bw/day Consumer DNEL, long-term dermal systemic 0,33 mg/kg bw/day Consumer DNEL, long-term dermal systemic 1,667 mg/kg bw/day Consumer DNEL, long-term oral systemic 0,333 mg/kg bw/day 88920-66-1 Alcohols, C16-18 and C18-unsatd., ethoxylated Consumer DNEL, long-term inhalation systemic 87 mg/m³ Consumer DNEL, long-term dermal systemic 1250 mg/kg bw/day Worker DNEL, long-term oral systemic 25 mg/kg bw/day Worker DNEL, long-term oral systemic 25 mg/kg bw/day Worker DNEL, long-term dermal systemic 25 mg/kg bw/day Worker DNEL, long-term inhalation systemic 294 mg/m³ 112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether Worker DNEL, long-term inhalation local 67,5 mg/m² Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term oral systemic 6,85 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term dermal systemic 9,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term dermal systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,966 mg/kg bw/day	Worker DNEL	, long-term	inhalation	systemic	5,7 mg/m³
Worker DNEL, long-term	68608-26-4	Sodium sulphonate			
Dw/day	Worker DNEL	, long-term	inhalation	systemic	0,66 mg/m³
Consumer DNEL, long-term inhalation systemic 0,33 mg/m³ Consumer DNEL, long-term dermal systemic 1,667 mg/kg bw/day Consumer DNEL, long-term oral systemic 0,833 mg/kg bw/day 66920-66-1 Alcohols, C16-18 and C18-unsatd, ethoxylated Tonsumer DNEL, long-term inhalation systemic 87 mg/m³ Consumer DNEL, long-term dermal systemic 1250 mg/kg bw/day Consumer DNEL, long-term oral systemic 25 mg/kg bw/day Worker DNEL, long-term dermal systemic 2080 mg/kg bw/day Worker DNEL, long-term inhalation systemic 294 mg/m³ 112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether Worker DNEL, long-term inhalation local 67,5 mg/m³ Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one worker DNEL, long-term inhalation systemic 0,966 mg/kg bw/day	Worker DNEL	, long-term	dermal	systemic	
bw/day	Consumer DN	EL, long-term	inhalation	systemic	
Consumer DNEL, long-term oral systemic 0,833 mg/kg bw/day 68920-66-1 Alcohols, C16-18 and C18-unsatd., ethoxylated Consumer DNEL, long-term inhalation systemic 87 mg/m³ Consumer DNEL, long-term dermal systemic 1250 mg/kg bw/day Consumer DNEL, long-term oral systemic 25 mg/kg bw/day Worker DNEL, long-term inhalation systemic 294 mg/m³ 112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether Worker DNEL, long-term inhalation local 67,5 mg/m³ Worker DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one worker DNEL, long-term inhalation systemic 6,81 mg/m³ Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,345 mg/kg bw/day Consumer DNEL, long-term inhalation systemic <td< td=""><td>Consumer DN</td><td>EL, long-term</td><td>dermal</td><td>systemic</td><td></td></td<>	Consumer DN	EL, long-term	dermal	systemic	
Consumer DNEL, long-term inhalation systemic 87 mg/m³ Consumer DNEL, long-term dermal systemic 1250 mg/kg bw/day Consumer DNEL, long-term oral systemic 25 mg/kg bw/day Worker DNEL, long-term dermal systemic 2080 mg/kg bw/day Worker DNEL, long-term inhalation systemic 294 mg/m³ 112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether Worker DNEL, long-term inhalation local 67,5 mg/m³ Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one worker DNEL, long-term inhalation systemic 6,81 mg/m³ Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one inhalation	Consumer DN	EL, long-term	oral	systemic	0,833 mg/kg
Consumer DNEL, long-term dermal systemic 1250 mg/kg bw/day Consumer DNEL, long-term oral systemic 25 mg/kg bw/day Worker DNEL, long-term dermal systemic 2080 mg/kg bw/day Worker DNEL, long-term inhalation systemic 294 mg/m³ 112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether Worker DNEL, long-term inhalation local 67,5 mg/m³ Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term inhalation systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 6,81 mg/m³ O,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one	68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated		·	
bw/day	Consumer DN	EL, long-term	inhalation	systemic	87 mg/m³
Worker DNEL, long-term inhalation systemic 294 mg/m³ 112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether Worker DNEL, long-term inhalation local 67,5 mg/m³ Worker DNEL, long-term inhalation local 101,2 mg/m³ Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 6,81 mg/m³ Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Consumer DN	EL, long-term	dermal	systemic	, -
Worker DNEL, long-term inhalation systemic 294 mg/m³ 112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether Worker DNEL, long-term inhalation local 67,5 mg/m³ Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 6,81 mg/m³ Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Consumer DN	EL, long-term	oral	systemic	25 mg/kg bw/day
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether Worker DNEL, long-term inhalation local 67,5 mg/m³ Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 6,81 mg/m³ Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Worker DNEL	, long-term	dermal	systemic	
Worker DNEL, long-term inhalation local 67,5 mg/m³ Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 6,81 mg/m³ Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Worker DNEL	, long-term	inhalation	systemic	294 mg/m³
Worker DNEL, acute inhalation local 101,2 mg/m³ Consumer DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 6,81 mg/m³ Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobut	yl ether		
Consumer DNEL, long-term oral systemic 6,25 mg/kg bw/day 2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 6,81 mg/m³ Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Worker DNEL	, long-term	inhalation	local	67,5 mg/m³
2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one Worker DNEL, long-term inhalation systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Worker DNEL	, acute	inhalation	local	101,2 mg/m³
2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	Consumer DN	EL, long-term	oral	systemic	
Worker DNEL, long-term dermal systemic 0,966 mg/kg bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-c	one	•	
bw/day Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Worker DNEL	, long-term	inhalation	systemic	6,81 mg/m³
Consumer DNEL, long-term inhalation systemic 1,2 mg/m³ Consumer DNEL, long-term dermal systemic 0,345 mg/kg bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Worker DNEL	, long-term	dermal	systemic	1
bw/day 2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Consumer DN	EL, long-term	inhalation	systemic	
2682-20-4 2-methylisothiazol-3(2H)-one Worker DNEL, long-term inhalation local 0,021 mg/m³	Consumer DN	EL, long-term	dermal	systemic	1
	2682-20-4	2-methylisothiazol-3(2H)-one			
Worker DNEL, acute inhalation local 0,043 mg/m³	Worker DNEL	, long-term	inhalation	local	0,021 mg/m³
	Worker DNEL	, acute	inhalation	local	0,043 mg/m³

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650 Revision date: 13.01.2025 Product code: 770046 Page 8 of 19

Consumer DNEL, long-term	inhalation	local	0,021 mg/m³
Consumer DNEL, acute	inhalation	local	0,043 mg/m³
Consumer DNEL, long-term	oral	systemic	0,027 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,053 mg/kg bw/dav

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 9 of 19

PNEC values

CAS No Substance	
Environmental compartment	Value
122-99-6 2-phenoxyethanol	·
Freshwater	0,943 mg/l
Freshwater (intermittent releases)	3,44 mg/l
Marine water	0,094 mg/l
Freshwater sediment	7,237 mg/kg
Marine sediment	0,724 mg/kg
Micro-organisms in sewage treatment plants (STP)	36 mg/l
Soil	1,31 mg/kg
68608-26-4 Sodium sulphonate	
Freshwater	1 mg/l
Freshwater (intermittent releases)	10 mg/l
Marine water	1 mg/l
Freshwater sediment	723500000 mg/kg
Marine sediment	723500000 mg/kg
Secondary poisoning	16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	868700000 mg/kg
68920-66-1 Alcohols, C16-18 and C18-unsatd., ethoxylated	
Freshwater	0,007 mg/l
Freshwater (intermittent releases)	0,1 mg/l
Marine water	0,001 mg/l
Freshwater sediment	22,79 mg/kg
Marine sediment	2,28 mg/kg
Micro-organisms in sewage treatment plants (STP)	10000 mg/l
Soil	1 mg/kg
112-34-5 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	
Freshwater	1,1 mg/l
Freshwater (intermittent releases)	11 mg/l
Marine water	0,11 mg/l
Freshwater sediment	4,4 mg/kg
Marine sediment	0,44 mg/kg
Secondary poisoning	56 mg/kg
Soil	0,32 mg/kg
2634-33-5 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	
Freshwater	0,00403 mg/l
Freshwater (intermittent releases)	0,0011 mg/l
Marine water	0,000403 mg/l
Freshwater sediment	0,0499 mg/kg
Marine sediment	0,00499 mg/kg
Micro-organisms in sewage treatment plants (STP)	1,03 mg/l

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650 Revision date: 13.01.2025 Product code: 770046 Page 10 of 19

Soil		3 mg/kg
26530-20-1	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]	
Freshwater		0,0022 mg/l
Freshwater (i	intermittent releases)	0,00122 mg/l
Marine water		0,00022 mg/l
Freshwater s	ediment	0,0475 mg/kg
Marine sedim	nent	0,00475 mg/kg
Soil		0,0082 mg/kg
2682-20-4	2-methylisothiazol-3(2H)-one	·
Freshwater		0,00339 mg/l
Freshwater (i	0,00339 mg/l	
Marine water	0,00339 mg/l	
Micro-organis	0,23 mg/l	
Soil		0,047 mg/kg

Additional advice on limit values

source:

Recommended limit value for cooling lubricants (steam and aerosol)

MAK: 10 mg/m³

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. full mask (DIN EN 136). Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 11 of 19

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: brown

Odour: like: mineral oil.
Odour threshold: not determined

Test method

Melting point/freezing point:

No data available

Boiling point or initial boiling point and

> 100 °C

boiling range:

Flammability:

Lower explosion limits:

No data available

Upper explosion limits:

No data available

Flash point: > 100 °C DIN EN ISO 2592

Auto-ignition temperature: > 240 °C
Decomposition temperature: No data available

pH-Value (at 20 °C): 9,0 4% - DIN 51369
Viscosity / kinematic: 300 mm²/s DIN EN ISO 3104

(at 20 °C)

Water solubility: highly soluble.

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

Density (at 15 °C): 0,974 g/cm³ DIN EN ISO 12185

Relative vapour density:

Particle characteristics:

No data available

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available
Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Pour point:

No data available

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 12 of 19

10.5. Incompatible materials

Reacts with: Oxidising agent, strong

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Sulphur dioxide (SO2).. Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 13 of 19

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
122-99-6	2-phenoxyethanol									
	oral	ATE 1394	mg/kg							
	dermal	LD50 mg/kg	>2000	Rabbit						
68608-26-4	Sodium sulphonate									
	oral	LD50 mg/kg	> 5000	Rat	Study report (1985)	OECD Guideline 401				
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1981)	OECD Guideline 402				
68920-66-1	Alcohols, C16-18 and C	18-unsatd., e	ethoxylated							
	oral	LD50 mg/kg	> 2000	Rat	Study report (1982)	OECD Guideline 401				
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	OECD Guideline 402				
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether									
	oral	LD50 mg/kg	5660	Rat						
	dermal	LD50 mg/kg	4120	Rabbit						
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one									
	oral	LD50 mg/kg	670	Rat	Study report (1988)	OECD Guideline 401				
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1994)	OECD Guideline 402				
26530-20-1	octhilinone (ISO); 2-octy	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]								
	oral	ATE 125	mg/kg							
	dermal	ATE 311								
	inhalation dust/mist ATE 0,27 mg/l									
2682-20-4	2-methylisothiazol-3(2H)									
	oral	LD50 mg/kg	120	Rat	Study report (2002)	EPA OPPTS 870.1100				
	dermal	LD50 mg/kg	242	Rat	Study report (1999)	OECD Guideline 402				
	inhalation vapour	ATE	0,5 mg/l							
	inhalation dust/mist	ATE	0,05 mg/l							

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]; 2-methylisothiazol-3(2H)-one)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 14 of 19

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Mixture not tested.

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 15 of 19

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
122-99-6	2-phenoxyethanol								
	Acute fish toxicity	LC50 460 mg/l	220 -	96 h	Leuciscus idus				
	Acute algae toxicity	ErC50 mg/l	> 500	72 h	Scenedesmus sp.				
	Acute crustacea toxicity	EC50 mg/l	> 500	48 h	Daphnia magna				
68608-26-4	Sodium sulphonate								
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	Study report (1994)	EPA OTS 797.1050		
8920-66-1	Alcohols, C16-18 and C18	8-unsatd., et	hoxylated						
	Acute fish toxicity	LC50	108 mg/l	96 h	Danio rerio	Study report (2008)	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (1997)	other: EU-Guideline 92/69/EWG		
	Acute crustacea toxicity	EL50	51 mg/l	48 h	Daphnia magna	Study report (2000)	OECD Guideline 202		
	Fish toxicity	NOEC mg/l	0,16	10 d	Pimephales promelas	Study report (1995)	The effect of the test substance or surv		
	Crustacea toxicity	NOEC mg/l	0,77	21 d	Daphnia magna	Publication (1999)	other: USEPA-TSCA		
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether								
	Acute algae toxicity	ErC50 mg/l	> 100		Scenedesmus sp.				
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna				
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one								
	Acute fish toxicity	LC50 mg/l	ca. 16,7	96 h	Cyprinodon variegatus	REACh Registration Dossier	other:		
	Acute algae toxicity	ErC50 mg/l	0,15	72 h	Raphidocelis subcapitata	Study report (1994)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	2,94	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202		
	Acute bacteria toxicity	EC50)	13 mg/l (3 h	activated sludge of a predominantly domestic sewag	REACh Registration Dossier	OECD Guideline 209		
26530-20-1	octhilinone (ISO); 2-octyl-	2H-isothiazo	I-3-one; [OI]	Γ]					
	Acute fish toxicity	LC50 mg/l	0,122	96 h		Study report (2018)	other: From Episuite v4.11		
	Acute algae toxicity	ErC50 mg/l	0,15	96 h		Study report (2018)	other: From Episuite v4.11		
	Acute crustacea toxicity	EC50 mg/l	0,181	48 h	Daphnia sp.	Study report (2018)	other: From Episuite v4.11		
2682-20-4	2-methylisothiazol-3(2H)-	one							
	Acute fish toxicity	LC50 mg/l	4,77	96 h	Oncorhynchus mykiss	REACh Registration Dossier	EPA OPP 72-1		
	+	+		+	 	+	+		

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650								
Revision date: 13.01.2025	Revision date: 13.01.2025 Product code: 770046							
Acute algae toxi	city ErC50 mg/l	0,069		Skeletonema costatum	Study report (2004)	EPA OPPTS 850.5400		
Acute crustacea	toxicity EC50 mg/l	0,934	48 h	Daphnia magna	REACh Registration Dossier	EPA OPP 72-2		
Fish toxicity	NOEC mg/l	4,93	98 d	Oncorhynchus mykiss	REACh Registration Dossier	EPA OPPTS 850.1400		
Crustacea toxici	ty NOEC mg/l	0,044	21 d	Daphnia magna	REACh Registration Dossier	EPA OPPTS 850.1300		
Acute bacteria to	exicity EC50	41 mg/l (activated sludge of a predominantly domestic sewag	REACh Registration Dossier	OECD Guideline 209		

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

Mixture not tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
122-99-6	2-phenoxyethanol	1,16
68608-26-4	Sodium sulphonate	18,05
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated	ca. 7,19
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	0,56 (25°C)
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	0,63
26530-20-1	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]	2,61
2682-20-4	2-methylisothiazol-3(2H)-one	-0,486

BCF

CAS No	Chemical name	BCF	Species	Source
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated	387,5	Pimephales promelas	Publication (2000)
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	ca. 6,62	Lepomis macrochirus	REACh Registration D
26530-20-1	octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; [OIT]	1,284	fish unspecified	Study report (2018)
2682-20-4	2-methylisothiazol-3(2H)-one	5,75	Lepomis macrochirus	REACh Registration D

12.4. Mobility in soil

Is eliminable from water only with difficulty.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 17 of 19

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

120107

WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:
14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number or ID number:
14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:

Marine transport (IMDG)

14.1. UN number or ID number:
14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 55, Entry 75

National regulatory information

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650

Revision date: 13.01.2025 Product code: 770046 Page 18 of 19

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3,4,5,6,7,8,9,10,12.

Abbreviations and acronyms

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified: NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program: OECD - Organization for Economic Co-operation and Development: PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Eye Dam. 1; H318	Calculation method	
Skin Sens. 1; H317	Calculation method	
Aquatic Chronic 3; H412	Calculation method	

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.		
H302	Harmful if swallowed.		
H311	Toxic in contact with skin.		

H314 Causes severe skin burns and eye damage.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Penta-Cool WM 650			
Revision date: 13.01.2025	Product code: 770046	Page 19 of 19	
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H330	Fatal if inhaled.		
H335	May cause respiratory irritation.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
EUH071	Corrosive to the respiratory tract.		

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)