

according to Regulation (EC) No 1907/2006

# **Ecoplus XT U**

Print date: 06.10.2015 Product code: 777021 Page 1 of 7

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Ecoplus XT U

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Use of the substance/mixture

Parting agent.

## 1.3. Details of the supplier of the safety data sheet

ADDINOL Lube Oil GmbH Company name:

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de Contact person: Application Technology Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

1.4. Emergency telephone +49 (0) 3461-845201 - This number is serviced during office hours.

number:

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

May be fatal if swallowed and enters airways.

## 2.2. Label elements

## Hazardous components which must be listed on the label

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Signal word: Danger GHS08 Pictograms:



## **Hazard statements**

H304 May be fatal if swallowed and enters airways.

#### **Precautionary statements**

IF SWALLOWED: Immediately call a POISON CENTER/doctor. P301+P310

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to a waste disposal system.

## Special labelling of certain mixtures

**EUH208** Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one. May produce an

allergic reaction.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

# **Ecoplus XT U**

Print date: 06.10.2015 Product code: 777021 Page 2 of 7

## Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## **Hazardous components**

EC No	Chemical name	Quantity			
CAS No	Classification according to Directive 67/548/EEC				
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
REACH No					
932-078-5	Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	< 20 %			
64742-46-7					
	Asp. Tox. 1; H304				
01-2119552497-29					
214-139-1	Morpholine oleate	< 5 %			
1095-66-5					
	Skin Irrit. 2, Eye Irrit. 2; H315 H319				
220-120-9	1,2-Benzisothiazol-3(2H)-on	< 0,1 %			
2634-33-5					
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 1); H302 H315 H318 H317 H400 H410				

Full text of R-, H- and EUH-phrases: see section 16.

#### **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

## After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

## After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

# **Ecoplus XT U**

Print date: 06.10.2015 Product code: 777021 Page 3 of 7

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

## 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eye and clothing.

## Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place.

## Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.





according to Regulation (EC) No 1907/2006

# **Ecoplus XT U**

Print date: 06.10.2015 Product code: 777021 Page 4 of 7

## Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. Recommended storage temperature: 10 - 30°C

#### 7.3. Specific end use(s)

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

## 8.2. Exposure controls





## Appropriate engineering controls

No special measures are necessary.

## Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

## Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

## Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

## Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm





according to Regulation (EC) No 1907/2006

# **Ecoplus XT U**

Print date: 06.10.2015 Product code: 777021 Page 5 of 7

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: white

Odour: characteristic

Test method

## Changes in the physical state

Density (at 20 °C): 0,97 g/cm³ DIN 51757

Water solubility: easily soluble.

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Stable with proper care and handling.

# 10.2. Chemical stability

The product is chemically stable when handled and stored under normal conditions.

## 10.3. Possibility of hazardous reactions

No decomposition if used as intended.

## 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

## 10.5. Incompatible materials

none

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### **Acute toxicity**

No data available

Mixture not tested.

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
2634-33-5	1,2-Benzisothiazol-3(2H)-on					
	oral	ATE	500 mg/kg			

## Irritation and corrosivity

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

# Sensitising effects

Evaluation: no danger of sensitization.

## Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

# **Ecoplus XT U**

Print date: 06.10.2015 Product code: 777021 Page 6 of 7

## Carcinogenic/mutagenic/toxic effects for reproduction

No data available

### Specific effects in experiment on an animal

No data available

## **SECTION 12: Ecological information**

## 12.1. Toxicity

No data available

Mixture not tested.

#### 12.2. Persistence and degradability

No data available

## 12.3. Bioaccumulative potential

No data available

## 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

## 12.6. Other adverse effects

No data available

#### **Further information**

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## Advice on disposal

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

#### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

<u>14.1. UN number:</u>

Inland waterways transport (ADN)

14.1. UN number:

Marine transport (IMDG)

<u>14.1. UN number:</u> -

Air transport (ICAO)

14.1. UN number:

## 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

## 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

# **Ecoplus XT U**

Print date: 06.10.2015 Product code: 777021 Page 7 of 7

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

#### Other applicable information

No dangerous good in sense of these transport regulations.

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

# Relevant H- and EUH-phrases (Number and full text)

	or princess (realises and rain text)
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one. May produce an allergic reaction

## **Further Information**

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contructual relationship.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)