according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Erosion Fluid ED 2 L

UFI: DSTU-X7HH-120U-GQVF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Erosion fluid.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Gidov Oil & Logistics Ltd.

Street: 76 Cobham Road, Ferndown Industrial Estate
Place: GB-TN157DA Wrotham, Sevenoaks Kent

Telephone: +44 7729229830 Telefax: +44 7729229830

e-mail: sales@addinol.co.uk

Internet: https://www.gidovlogistics.co.uk/

1.4. Emergency telephone +44 7729229830 - This number is serviced during office hours.

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.

according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 2 of 9

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to industrial incineration plant.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics			> 90 - 100 %
	920-107-4		01-2119453414-43	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Specific Conc. Limits, M-factors and ATE	
	920-107-4	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	> 90 - 100 %
	dermal: LD50 = >= 3160 mg/kg; oral: LD50 = > 15000 mg/kg		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove/Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids

according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 3 of 9

apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Caution if victim vomits: Risk of aspiration!

Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

after ingestion: Coughing. shortage of breath.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Atomized water. Water fog. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon monoxide Nitrogen oxides (NOx). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered,

Print date: 20.06.2023

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 4 of 9

arrangements with local exhaust ventilation have to be used. Use only antistatically equipped (spark-free) tools. Do not put any product-impregnated cleaning rags into your trouser pockets. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Provide adequate ventilation as well as local exhaustion at critical locations. Take precautionary measures against static discharges. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Material, rich in oxygen, oxidizing.

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: UV-radiation/sunlight. frost. heat. Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Recommended limit value for cooling lubricants (steam and aerosol)

MAK: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 5 of 9

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liauid Colour: colourless Odour. like: paraffin. Odour threshold: not determined

Test method

Melting point/freezing point: No data available Boiling point or initial boiling point and

230 °C

boiling range:

Flammability: No data available 0,5 vol. % Lower explosion limits: Upper explosion limits: 5 vol. %

Flash point: 102 °C DIN EN ISO 2592 220 °C ASTM E 659 Auto-ignition temperature:

Decomposition temperature: No data available pH-Value: not applicable

Viscosity / kinematic: 2,3 mm²/s DIN EN ISO 3104

(at 40 °C)

Water solubility: insoluble

Solubility in other solvents No data available

Partition coefficient n-octanol/water: No data available Vapour pressure: No data available

Density (at 15 °C): 0,817 g/cm3 DIN EN ISO 12185

Relative vapour density: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties No data available Self-ignition temperature

> No data available Solid: Gas: No data available

Oxidizing properties No data available

Other safety characteristics

Evaporation rate: No data available

Pour point: -20 °C ISO 3016

Print date: 20.06.2023

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 6 of 9

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Do not overheat to avoid decomposition by heat.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon monoxide Nitrogen oxides (NOx). carbon black. No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
	Hydrocarbons, C12-C15,	n-alkanes, isoalkanes, c	yclics, < 2% aromatics			
	oral	LD50 > 15000 mg/kg	Rat	Study report (1977)	OECD Guideline 401	
	dermal	LD50 >= 3160 mg/kg	Rabbit	Study report (1984)	OECD Guideline 402	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 7 of 9

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name					
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
	Hydrocarbons, C12-C15,	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna		
	Crustacea toxicity	NOEC mg/l	> 1000	21 d	Daphnia magna	REACh Registration Dossier	The aquatic toxicity was estimated by a

12.2. Persistence and degradability

Product is partially biodegradable.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>= 5,03

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>= 207,7		REACh Registration D

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

Print date: 20.06.2023

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 8 of 9

120107

WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be thrown away. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number or ID number:
14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:

Marine transport (IMDG)

14.1. UN number or ID number:
14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

according to UK REACH Regulation

ADDINOL Erosion Fluid ED 2 L

Revision date: 20.06.2023 Product code: 782030 Page 9 of 9

This data sheet contains changes from the previous version in section(s): 9.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations), ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n:o:s: - Not Otherwise Specified: NFPA - National Fire Protection Association: NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS -Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)