according to Regulation (EC) No 1907/2006

**ADDINOL Penta-Cool WM 930** 

Revision date: 25.03.2020

Product code: 770104

Page 1 of 10

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

ADDINOL Penta-Cool WM 930

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/mixture

Metal working fluids.

## 1.3. Details of the supplier of the safety data sheet

# Manufacturer

	Manufacturer		
	Company name:	ADDINOL Lube Oil GmbH	
		Gebäude 4609	
	Street:	Am Haupttor	
	Place:	D-06237 Leuna	
	Telephone:	+49 (0) 3461 845-0	Telefax:+49 (0) 3461 845-555
	e-mail:	info@addinol.de	
	Contact person:	Application Technology	
	Internet:	www.addinol.de	
	Responsible Department:	ADDINOL Application Technology	
	Supplier		
	Company name:	Specialised Products (Western) Limited	
	Street:	76 Cobham Road, Ferndown Industrial Estate,	
	Place:	GB-BH21 7RN Wimborne, Dorset	
	Telephone:	+44 1202 891393	Telefax:+44 1202 876908
	e-mail:	sales@specialisedproducts.co.uk	
	Internet:	http://specialisedproducts.co.uk	
1	.4. Emergency telephone	+44 1202 891393 - This number is serviced du	ring office hours.
	unale a m		-

## number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

# Regulation (EC) No. 1272/2008

Hazard categories: Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

## 2.2. Label elements

### Regulation (EC) No. 1272/2008

Signal word:

Pictograms:



according to Regulation (EC) No 1907/2006

# **ADDINOL Penta-Cool WM 930**

Revision date: 25.03.2020

Product code: 770104

Page 2 of 10

# Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

## Precautionary statements

ouulionaly olulonio	
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container to industrial incineration plant.

## Special labelling of certain mixtures

Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction.

## Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

# 2.3. Other hazards

EUH208

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

according to Regulation (EC) No 1907/2006

**ADDINOL Penta-Cool WM 930** 

Revision date: 25.03.2020

Product code: 770104

Page 3 of 10

### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification	•	•	
112-34-5	2-(2-Butoxyethoxy)ethanol			<5 %
	203-961-6		01-2119475104-44	
	Eye Irrit. 2; H319			
122-99-6	2-Phenoxyethanol			<5 %
	204-589-7		01-2119488943-21	
	Acute Tox. 4, Eye Dam. 1, STOT			
68920-66-1	Alcohols, C16-18 and C18-unsat	< 5 %		
	500-236-9		01-2119489407-26	
	Skin Irrit. 2, Aquatic Chronic 2; H			
78-96-6	1-aminopropan-2-ol; isopropano	< 3 %		
	201-162-7	603-082-00-1		
	Skin Corr. 1B; H314			
95-14-7	1,2,3-Triazaindene			<1 %
	202-394-1			
	Acute Tox. 4, Eye Irrit. 2, Aquation	Chronic 2; H302 H319 H41	1	
4299-07-4	2-n-butyl-benzo[d]isothiazol-3-or	<0,5 %		
	420-590-7	606-079-00-3		
	Skin Corr. 1B, Skin Sens. 1, Aqu	atic Acute 1, Aquatic Chroni	c 1; H314 H317 H400 H410	

Full text of H and EUH statements: see section 16.

### Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

### SECTION 4: First aid measures

### 4.1. Description of first aid measures

### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets. When in doubt or if symptoms are observed, get medical advice.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Use skin protection ointment after cleaning. In case of skin irritation, seek medical treatment.

## After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Call a physician immediately. Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

according to Regulation (EC) No 1907/2006

**ADDINOL Penta-Cool WM 930** 

Revision date: 25.03.2020

Product code: 770104

Page 4 of 10

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### **4.3. Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Foam. Extinguishing powder. Atomized water. Carbon dioxide (CO2).

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). Phosphorus oxides. carbon black.

## 5.3. Advice for firefighters

Keep away from unprotected people. Keep upwind. In case of fire: Wear self-contained breathing apparatus.

### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

### Advice on safe handling

Use personal protection equipment. Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eye and clothing.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

according to Regulation (EC) No 1907/2006

# **ADDINOL Penta-Cool WM 930**

Revision date: 25.03.2020

Product code: 770104

Page 5 of 10

Keep away from: Oxidizing agents.

# Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. Recommended storage temperature: 5 - 40°C

# 7.3. Specific end use(s)

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL

## **DNEL/DMEL** values

CAS No	Substance					
DNEL type	DNEL type		Effect	Value		
122-99-6	2-Phenoxyethanol					
Worker DNEL, long-term		dermal	systemic	34,72 mg/kg bw/day		
Worker DNEL,	long-term	inhalation	systemic	8,07 mg/m³		
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated					
Worker DNEL, long-term		dermal	systemic	2080 mg/kg bw/day		
Worker DNEL,	Worker DNEL, long-term		systemic	294 mg/m³		

## **PNEC** values

CAS No	Substance				
Environmental compartment Value					
122-99-6	2-Phenoxyethanol				
Freshwater		0,943 mg/l			
Marine water 0,0943 mg					
Freshwater sediment 7,2366 mg/kg					
Marine sediment 24,8					
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated				
Freshwater		0,0327 mg/l			
Marine water 0,00327 mg/k					
Freshwater sediment 0,177 mg/kg					
Micro-organism	s in sewage treatment plants (STP)	3,3 mg/l			

## Additional advice on limit values

source:

Recommended limit value for cooling lubricants (steam and aerosol) MAK: 10  $\mbox{mg/m}^3$ 

# 8.2. Exposure controls

according to Regulation (EC) No 1907/2006

## **ADDINOL Penta-Cool WM 930**

Revision date: 25.03.2020

Product code: 770104

Page 6 of 10





### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

### Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

## **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. full mask (DIN EN 136). Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

a. I. mormation on basic physical and thei	mear properties		
Physical state:	liquid		
Colour:	light brown		
Odour:	characteristic		
			Test method
pH-Value (at 20 °C):		9,7 (c = 5.5%)	DIN 51369
Changes in the physical state			
Melting point:		-20 °C	
Initial boiling point and boiling range:		> 100 °C	
Pour point:		-5 °C	
Flash point:		> 100 °C	DIN EN ISO 2592
Sustaining combustion:			UN Test L.2
Flammability			
Solid:		No data available	
Gas:		No data available	
Explosive properties			
not Explosive.			

according to Regulation (EC) No 1907/2006

0,6 vol. % 6,5 vol. % > 240 °C No data available		
> 240 °C		
No data available		
No data available		
No data available		
No data available		
0,978 g/cm³	DIN EN ISO 12185	
highly soluble.		
No data available		
178 mm²/s	DIN EN ISO 3104	
No data available		
No data available		
	No data available No data available 0,978 g/cm³ highly soluble. No data available 178 mm²/s No data available	No data available No data available 0,978 g/cm³ DIN EN ISO 12185 highly soluble. No data available 178 mm²/s DIN EN ISO 3104 No data available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

## 10.3. Possibility of hazardous reactions

No known hazardous reactions.

## 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

### 10.5. Incompatible materials

Reacts with : Oxidizing agents, strong.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). Phosphorus oxides. carbon black.

## **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

## Acute toxicity

Mixture not tested.

according to Regulation (EC) No 1907/2006

# **ADDINOL Penta-Cool WM 930**

Revision date: 25.03.2020

Product code: 770104

Page 8 of 10

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
122-99-6	2-Phenoxyethanol	2-Phenoxyethanol							
	oral	ATE mg/kg	500						
78-96-6	1-aminopropan-2-ol; isopropanolamine								
	oral	LD50 mg/kg	2700	Rat					
	dermal	LD50 mg/kg	1600	Rabbit					
95-14-7	1,2,3-Triazaindene								
	oral	ATE mg/kg	500						

## Irritation and corrosivity

Irritant effect on the eye: irritant. Irritant effect on the skin: irritant.

## Sensitising effects

Contains: 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

## STOT-repeated exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

No data available

Mixture not tested.

CAS No	Chemical name						
	Aquatic toxicity	Dose	Dose		Species	Source	Method
78-96-6	1-aminopropan-2-ol; isopropanolamine						
	Acute fish toxicity	LC50 460 mg/l	220 -	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50	23 mg/l		Desmodesmus subspicatus	IUCLID	
	Acute crustacea toxicity	EC50 mg/l	108,8	48 h	Daphnia	IUCLID	

## 12.2. Persistence and degradability

Part of the components is biodegradable.

### 12.3. Bioaccumulative potential

No data available

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-96-6	1-aminopropan-2-ol; isopropanolamine	-0,96

## 12.4. Mobility in soil

Is eliminable from water only with difficulty.

### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

according to Regulation (EC) No 1907/2006

**ADDINOL Penta-Cool WM 930** 

Revision date: 25.03.2020

Product code: 770104

Page 9 of 10

# 12.6. Other adverse effects

No data available

# Further information

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

### List of Wastes Code - residues/unused products

120107 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

## Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

<u>14.1. UN number:</u>	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-

Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Marine transport (IMDG)	
<u>14.1. UN number:</u>	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number:</u>	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	no
14.6. Special precautions for user	

Unless specified otherwise, general measures for safe transport must be followed.

according to Regulation (EC) No 1907/2006

**ADDINOL Penta-Cool WM 930** 

Revision date: 25.03.2020

Product code: 770104

Page 10 of 10

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# Other applicable information

No dangerous good in sense of these transport regulations.

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 55: 2-(2-Butoxyethoxy)ethanol

### National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

## Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction.

#### **Further Information**

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)